

150 Speedster®

Intuitive handling and intense maneuverability. All driven by a Rotax 4-TEC engine with the choice of a 155, 215 or 255 hp.

PERFORMANCE | 2009



Black / Yellow

Specifications

DIMENSIONS

Length	15' 4" / 4.67 m
Beam	.7' 1" / 2.16 m
Draft	12" / 30.5 cm
Dry weight	1,454 lbs / 659 kg
Seating capacity	4
Fuel capacity	21 US gal / 79.4 L

ENGINE

Model	Rotax® 1503 4-TEC®
Horsepower	155 hp, 215 hp or 255 hp

Highlights

- Digital Information Center w/19 functions including compass, water temperature, hour meter, depth finder
- Satellite-ready AM/FM/CD stereo w/MP3 port and 2 speakers
- Chrome cleats (4)
- Non-slip grab handles (8)
- Driver console
- Front and rear lockable storage
- Swim platform w/ladder
- Depth finder
- Ski pylon



Digital information center



Satellite-ready AM/FM/CD stereo with MP3 port



Lockable rear storage



Rotax 4-TEC engine

150 Speedster

PERFORMANCE | 2009



Overall Specifications

DIMENSIONS

Length	15' 4" / 4.67 m
Beam	7' 1" / 2.16 m
Draft	12" / 30.5 cm
Dry weight	1,454 lbs / 659 kg
Storage capacity	14.5 cu ft / .44 cu m
Seating capacity	4
Weight capacity	715 lbs / 324 kg
Fuel capacity	21 US gal / 79.4 L

DIMENSIONS (ON TRAILER)

Length	17' 5" / 5.22 m
Width	7' 1" / 2.16 m
Height: No tower	4' 11" / 1.50 m
Tower down	6' 10" / 2.08 m
Tower up	8' 4" / 2.54 m
Gross weight	2,100 lbs / 952 kg

ENGINE

Model	Fuel injected, Rotax 1503 4-TEC
Displacement	1,494 cc
Horsepower: Std	155 hp NA
Opt 1	215 hp SCIC
Opt 2	255 hp SCIC
Cylinders (/engine)	3
Max RPM (/engine): Std	7,300
Opt 1 & 2	8,000
Octane no: Std	87
Opt 1 & 2	91
Emission level	CARB 3-Star
Cooling system	Closed-Loop Cooling System

ELECTRICAL

Generator	30 amp / 380 W
Battery	12 V

HULL & DECK

Material	Composite FRP
Vinylester barrier layer	Std
Full fiberglass stringer	Std
Graphics	Std
Deadrise	20°
Colors: Opt 1 gel-coat	Black hull / Yellow graphics
Opt 2 gel-coat	Black hull / Red graphics

PROPULSION

Jet pump type:	
Axial flow	Single stage
Pump diameter: Std	6 1/8" / 15.56 cm
Opt 1 & 2	6 1/4" / 15.63 cm
Impeller:	
Material	Stainless steel
Outside diameter (mm)	159 ± .07
Reverse system	Std

Equipment

HULL & DECK

- Stringer system – composite FRP, foam filled
- Cleats – chrome (4)
- Cup holders (4)
- Rub rail (Black)
- Grab handles (8)
- Non-skid decking
- Navigation light – bow side lights
- Ski Pylon – Pull-up
- Tow eyes – stainless steel bow & stern
- Reboarding ladder – rear (1-step)
- Engine access – sunpad
- Engine blower
- Auto bilge pump

STORAGE

- Ski locker, lockable
- Sunpad, lockable
- Console, lockable

CONTROL STATION

HELM

- Steering – standard
- Separated shift & throttle lever
- Battery switch
- Fuse box
- DESS magnetic lanyard key

CONTROL STATION (Cont'd)

DIGITAL INFOCENTER

- Fuel level
- Low fuel level
- Low oil level
- Low voltage
- Tachometer
- Overheat
- Hour meter
- Maintenance info
- Speedometer
- Compass
- Water temperature
- Check engine
- Low oil pressure
- Depth Finder
- Sensor check
- Hi voltage
- Battery Protection
- Key (Wrong Key)
- L- Key

COCKPIT

- Dash finish – Black
- Outlet – 12 volt accessory (1)
- Cooler – integrated

STEREO & SOUND

- Stereo system – satellite-ready
- Speakers – stern (2)
- MP3 port

CANVAS & MISCELLANEOUS

- Warranty (1 yr)

CERTIFICATIONS

- NMMA
- CE

TRAILER

- Single axle
- Swing-away tongue
- Galvanized trailer

Options

- Wakeboard tower & racks
- Carpet – snap-in
- Mirror – with tower only
- Mooring cover
- Bimini top (incl. with tower)
- Custom trailer
- Warranty (3 years)

