

200 Speedster®

An aggressive, agile beast with up to 430 hp and the good looks to match.

PERFORMANCE | 2009



Bright White

Specifications

DIMENSIONS

Length	19' 9" / 6.02 m
Beam	8' / 2.44 m
Draft	12" / 30.5 cm
Dry weight: No tower	2,770 lbs / 1,256 kg
With tower	2,830 lbs / 1,284 kg
Seating capacity	7
Fuel capacity	44 US gal / 166.5 L

ENGINE

Model	Rotax® 1503 4-TEC® [x 2]
Horsepower	430 hp

Highlights

- Swim platform w/2-step ladder
- Dual rear storage compartment
- Sun deck pad
- Pop-up ski pylon
- Cockpit courtesy lights
- Ski storage
- Satellite-ready AM/FM/CD stereo w/MP3 port and 4 speakers
- Depth finder
- 12 volt jack
- Windscreen w/pop-up wind deflector and helm storage
- Built-in cooler
- Multi-function aluminum black rails
- Grab handles
- On-board storage



Full instrumentation dash with built-in cooler



Satellite-ready AM/FM/CD stereo with MP3 port



Pull-up ski pylon

200 Speedster

PERFORMANCE | 2009



Overall Specifications

DIMENSIONS

Length	19' 9" / 6.02 m
Beam	8' / 2.44 m
Draft	12" / 30.5 cm
Dry weight: No tower	2,770 lbs / 1,256 kg
With tower	2,830 lbs / 1,284 kg
Storage capacity	46 cu ft / 1.3 cu m
Seating capacity	7
Weight capacity	1,365 lbs / 619 kg
Fuel capacity	.44 US gal / 166.5 L

DIMENSIONS (ON TRAILER)

Length [tongue folded]	21' 2" / 6.45 m [18' 11" / 5.77 m]
Width	8' 6" / 2.59 m
Height: No tower	6' 6" / 1.98 m
Tower down	7' 1" / 2.16 m
Tower up	9' 11" / 3.02 m
Gross weight: No tower	4,095 lbs / 1,858 kg
With tower	4,115 lbs / 1,885 kg

ENGINE

Model	Fuel injected, Rotax 1503 4-TEC (2)
Displacement	1,494 cc
Horsepower	430 hp SCIC
Cylinders (/engine)	3
Max RPM (/engine)	8,000
Octane no.	91
Emission level	CARB 3-Star
Cooling system	Closed-Loop Cooling System

ELECTRICAL

Generator	30 amp / 380 W
Battery	12 V

HULL & DECK

Material	Composite FRP
Vinylester barrier layer	Std
Full fiberglass stringer	Std
Graphics	Std
Deadrise	21°
Colors: Opt 1 gel-coat	Red hull / White deck
Opt 2 gel-coat	White hull / White deck

PROPULSION

Jet pump type:	Single stage
Axial flow	Single stage
Pump diameter	6 1/4" / 15.63 cm
Impeller:	
Material	Stainless steel
Outside diameter (mm)	159 ± .07
Reverse system	Std

Equipment

HULL & DECK

- Stringer system – composite FRP, foam filled
- Cleats – chrome (6)
- Cup holders (6)
- Rub rail (Black)
- Grab handles (8)
- Non-skid decking
- Navigation light – bow side lights
- Courtesy lights (3)
- Ski pylon – pull-up
- Tow eyes – stainless steel bow & stern
- Reboarding ladder – rear (2-step)
- Engine access
- Engine blower (2)
- Auto bilge pump

STORAGE

- Anchor
- Ski locker, lockable
- Under seat
- Sunpad, lockable
- Glovebox, lockable

CONTROL STATION

HELM

- Steering – Custom
- Horn
- Separated shift & throttle lever
- Battery switch – rear storage
- Fuse box
- DESS magnetic lanyard key

INSTRUMENTATION

- Gauges – backlight & anti-fog
- Fuel level
- Overheat engine warning
- Speedometer – 88 mm
- Tachometer – 88 mm (2)
- Analog fuel – 47 mm
- Depth finder

COCKPIT

- Dash finish – Pearlstone
- Outlet – 12 volt accessory (1)
- Cooler – integrated

SEATING

Driver Seat

- Track & swivel

Passenger Seat

- Track & swivel

STEREO & SOUND

- Stereo system – satellite-ready
- Speakers – cockpit (4)
- MP3 port

CANVAS & MISCELLANEOUS

- Wind deflector
- Warranty (1 yr)

CERTIFICATIONS

- NMMA
- CE

TRAILER

- Single axle
- Disc brakes
- Swing-away tongue
- Galvanized trailer

Options

- Wakeboard tower & racks
- Carpet – snap-in
- Mirror – with tower only
- Mooring cover
- Bimini top
- Custom trailer
- Warranty (3 years)

